

### 4 to 8 mesh and 8 to 12 mesh White to Violet indicating.

### MSDS Ref MH 22102010IntWV

Version 1

# **1. Product Identification**

Brand name: Intersorb WV
Description: White to Violet, indicating Carbon Dioxide absorbent: Solid white granules formed from a combination of Calcium Hydroxide and Sodium Hydroxide.
Synonyms: None
CAS No.: Not applicable to mixtures.
Molecular Weight: Not applicable to mixtures.
Chemical Formula: Not applicable to mixtures.
Product Codes: 2181011, 2181016, 2181022
For information call: 0044(0)1189656300

# 2. Composition/ Information on ingredients.

## **Composition/ Information on ingredients.**

Ingredient	CAS No	Content	<b>Risk Phrase</b>	Hazard
		(% weight)		Symbol
Calcium	1305-62-0	75 - 80 %	R41	Xi
Hydroxide				
Sodium	1310-73-2	Under 4 %	R35	С
Hydroxide				
Ethyl Violet	2390-59-2	Under 0.1 %	R22/41	Xn
Water		13.5 – 17.5 %		

Intersorb WV contains no ozone depleting chemicals and no volatile organic chemical. During manufacture no ozone depleting chemicals or volatile organic chemical are used.



Crane House Molly Millars Lane Wokingham Berkshire RG41 2RZ T: +44 (0) 118 9656 300 F: +44 (0) 118 9656 356 Contact Number for Quality and Specialist information: 0044(0)1189 656361 'mhol@intersurgical.co.uk'. www.intersurgical.com info@intersurgical.co.uk

## 3. Hazards Identification

Health rating: Slight. Flammability rating: None. Reactivity rating: Slight. Lab Protective Equip: Dust mask recommended, General purpose rubber gloves, Goggles, Wash after skin contact.

Nature of hazard of finished mixture,

'Xi' Irritant

#### Risk phrases for finished mixture,

R41 Risk of serious damage to eyes. R 36/37/38Irritating to eye, respiratory system and skin.

#### **Safety Phrases:**

S2 Keep out of reach of children, S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S 37/39 Wear suitable gloves and eye/face protection. S 45 In case of accident or if you feel unwell seek medical advice immediately and show label if possible.

Dangerous Component determining label and risk phrases Sodium Hydroxide ( under 4 % weight ).

### 4. First Aid Measures.

**Eyes:** Get medical aid immediately. Do NOT allow victim to rub or keep eyes closed. Extensive irrigation with water is required (at least 30 minutes). **Skin:** Get medical aid immediately. Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Remove contaminated clothing in a manner which limits further exposure. Remove contaminated clothing and shoes. Thoroughly clean clothes and shoes before re-use. **Ingestion:** Do NOT induce vomiting. If victim is conscious and alert, give copious quantities of water. Never give anything by mouth to an unconscious person. Get medical aid immediately.

Inhalation: Get medical aid immediately. Remove from exposure and move to fresh air immediately.

# 5. Fire Fighting Measures.

**Fire:** Product is not considered to be a fire hazard. Packaging may be combustible. **Explosion:** Not considered to be an explosion hazard.

**Extinguishing Media:** Use extinguishing media that is appropriate for the environment. Do not get water inside containers and take care of resulting alkaline water

Flash Point: Not applicable, material is considered to be non-combustible.

NOTE: CO<sub>2</sub> is not suitable as extinguishing media: Exothermic reaction may occur.

#### 6.Accidental release measures.

**Health precautions**. Do not inhale released dust. Use dust mask type 3M 8710E. Use proper personal protective equipment as indicated in Section 8.

Environmental considerations. Do not discharge into sewer system.

**Spills/Leaks:** Vacuum or sweep up material and place into a suitable disposal container. Avoid generating dusty conditions. Do not get water inside containers.

## 7. Handling and Storage.

Handling: Wash thoroughly after handling.

Use with adequate ventilation and dust extractor if necessary. Minimize dust generation and accumulation. Do not get in eyes, on skin, or on clothing. Do not ingest or inhale. Do not allow contact with water. Keep from contact with moist air and steam.

Storage: Store in a tightly closed container.

Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from strong acids. Store protected from moisture.

Store at temperatures ranging from  $-20^{\circ}$ C to  $+50^{\circ}$ C. Do not allow to desiccate (dry out). Facilities storing or utilizing this material should be equipped with an eyewash facility.

## 8. Exposure Controls

Follow instructions for use when handling Intersorb WV

Exposure limits of components where relevant.

CAS No	Material	Occupational Exposure Limit.
1305-62-0	Calcium Hydroxide	5 mg/m <sup>3</sup> 8-hour time weighted average.
1310-73-2	Sodium Hydroxide	2 mg m <sup>3</sup> Short Term Exposure Limit.

#### **Personal Protective Equipment**

Eyes: Wear chemical safety goggles.

Skin: Wear appropriate gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

**Respirators:** Not necessary as product is provided in pellet form. If dust is generated, use dust mask type 3M 8710E.

# 9. Physical and Chemical Properties.

Physical State: Solid extrudates of 3 mm diameter.

Appearance: White Odor: None. pH: Basic in solution Bulk density: 830 – 860 g/l. Solubility in water: Less than 1 g/l at room temperature. Decomposition Temperature where relevant: Calcium Hydroxide decomposes to CaO at approximately 500°C. Sodium Hydroxide decomposes to Na<sub>2</sub>O at very high temperatures. Molecular Formula: Mixture of chemicals - see section 2

### 10. Stability and reactivity.

**Chemical Stability:** Stable at room temperature. Substance readily absorbs carbon dioxide from air.

**Conditions to Avoid:** Avoid contact with acids – vigorous reactions are possible. Do not use with trichloroethylene and chloroform.

Contact with high concentration of Carbon Dioxide will generate high temperatures. **Materials to avoid**:Hydrogen gas may be formed when in contact with some metals. **Hazardous Decomposition Products:** Toxic fumes of sodium oxide, calcium oxide. Low level of Amines may be released from decomposition of Ethyl Violet.

### **11. Toxicological Information.**

No toxicity data is available for finished mixture. However,

Toxicity of major component.

CAS No	Material	Acute toxicity.
1305-62-0	Calcium Hydroxide	LD50 <sup>rat</sup> of 7,300 mg/Kg

Toxicity of minor components.

CAS No	Material	Acute toxicity.
1310-73-2	Sodium Hydroxide	LD50 rabbit 500 mg/kg (
		10 % solution )

### 12. Ecological information.

Intersorb WV is not expected to significantly bio accumulate. Converts to naturally occurring materials. Do not discharge into lakes, rivers of sewer systems. When handled properly, Intersorb WV is not likely to prove detrimental to the environment.

### 13. Disposal Consideration.

Unused and utilized soda lime can be disposed of as commercial solid waste similar to household waste in accordance with local waste disposal regulations.

European Waste Catalogue Category: Waste packaging, Absorbents, Wiping cloths, filter materials and protective clothing. EAK No 150203: Absorbents.

# **14. Transport Information.**

Intersorb WV is not a dangerous product and may be sent by air, road, sea or post.

Transport Classification	Irritant
UN Number	None.
Hazard Class	None.
Packaging group	III low danger

## **15. Regulatory Information**

**Identification symbol and indication of danger.** Xi Irritant

#### **Risk Phrases**

R41 Risk of serious damage to eyes. R 36/37/38Irritating to eye, respiratory system and skin.

#### Dangerous Component determining label and risk phrases.

Sodium Hydroxide ( under 4 % weight )

#### Safety Phrases.

S2 Keep out of reach of children, S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S 37/39 Wear suitable gloves and eye/face protection. S 45 In case of accident or if you feel unwell seek medical advice immediately and show label if possible.

## 16. Other information.

The intended use of this product is as an absorbent for Carbon Dioxide. It is suitable for use within anaesthetic equipment.

The above information represents our current state of experience and is provided in good faith. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person. It is the responsibility of the customer to test whether the product is suitable for the purpose intended by the customer.

Date of issue 22<sup>nd</sup> October 2010 Contact: Mike Holder. Tel: Quality and specialist information 0044(0)1189656361 e-mail 'mhol@intersurgical.co.uk' or general 'info@intersurgical.co.uk'